


1008131020

TKIS-2

VoIP Intercom Module



- ✓ Build your own IP Intercom station or Help-Point
- ✓ Make your own 10W IP Speaker
- ✓ Control relay and I/Os over IP
- ✓ Supports Exigo, AlphaCom, IC-EDGE and SIP (for use with any IPBX)
- ✓ Supports a wide set of IP networking standards
- ✓ ONVIF Compatible
- ✓ Add VoIP/CCoIP to your parking solution, cash point, vending machine, et al
- ✓ Remote software upgrade, configuration and monitoring
- ✓ Powered over Ethernet (PoE)

 Avaya Certified


CISCO Certified



UL Certified Intercom



Turbine



ICX-AlphaCom



Exigo



Automatic Volume



Automatic Gain Control



Active Noise Cancelling







Open Duplex

Description

The VoIP Intercom Module utilizes the latest technology to create unparalleled audio quality. Some of the many features include: HD voice quality, Open Duplex, Active Noise Cancellation, Automatic Volume Adjustment, MEMS microphone support, and a 10W Class D amplifier. These features, in conjunction with Vingtor-Stentofon's 70 years of experience with acoustic technology are only a few of the many factors that make our audio quality second to none.

See also: [additional documentation on wiki.zenitel.com](https://wiki.zenitel.com)

Technical Dimensions



Specifications

AUDIO

Noise cancelling - suppression of musical noise	YES
Noise cancelling - suppression of static noise	YES
Noise cancelling - suppression of rapidly changing noise	YES
Codecs	G.711, G.722, G.729
Frequency range, G.722 Codec	200 Hz – 7000 Hz
Audio technology	Modes: Full open duplex, switched open duplex, Adaptive jitter filter, Local tone generator, Audio mixing - 3 channels, Sound level detection (scream alarm), Automatic gain control (microphone), Automatic volume adjustment
Internal speaker amplifier	10 W class D
Supported microphone technologies	Digital MEMS, omnidirectional microphone. Electret omnidirectional microphone
Recommended loudspeaker impedance	8 ohm

HARDWARE

Ethernet connector	1 x RJ 45
All other connectors	Tool less, spring loaded, vibration proof terminals
General inputs and outputs	6 (configurable)
Outputs	12mA as LED drivers
Change-over relay (NO+NC+COM)	Max: 250VAC/220VDC, 2A, 60W
Power options	PoE and or external power supply
PoE (power over Ethernet)	IEEE 802.3af standard, Class 0 (0.44W to 12.95 W)
External power supply	24 VDC (16 – 48 V)
Power consumption	Idle 1.8W, max 12W (depending on volume)
Audio line out / induction loop signal	600 Ohm

NETWORKING AND PROTOCOLS

Protocols	IPv4 (with DiffServ), SIP, TCP, UDP, HTTPS, TFTP, RTP, DHCP, SNMP, ONVIF, CCoIP®, NTP
LAN protocols	Power over Ethernet (IEEE 802.3 a-f) Network Access Control (IEEE 802.1x)
Management and operation	HTTP/HTTPS (Web configuration) DHCP and static IP + IC-EDGE. Remote automatic software upgrade. Centralized monitoring
Advanced supervision functions	E.g. network test, tone test, status reports
SIP support	RFC 3261 (SIP base standard), RFC 3515 (SIP refer), RFC 2976 (SIP info)
DTMF support	RFC 2833, 2976 (SIP info)

ENVIRONMENT AND COMPLIANCES

Operating temperature range	-40° to 70° C / -40° to 158 ° F
Storage temperature range	-40° to 70° C / -40° to 158 ° F
Relative humidity	< 95% not condensing
EMC	CE and FCC Part 15
Certificates	UL 60950-1, cUL 60950-1, CB to IEC 60950-1

OTHER SPECIFICATIONS

IP address information	Speaks IP address after system boot (requires connected loudspeaker)
Country of manufacture	Poland
Dimensions (HxWxD)	32 x 117 x 71 mm
Weight	0.1 kg / 0.2 lbs
Encapsulation material	ASA plastic
DIN-rail clips	Wago 209 (included)

Accessories



TA-16



10 pcs.

TA-17



IP-LCM-A

IP Line Expansion Module with Inputs/Outputs

Used With



TKIA-2

Analog over IP Gateway



TCIA-2

Analog over IP Intercom



TCIA-2-P

Package with TCIA-2,TKIA-2,TKIS-2